

Certified Product List - Residential

2020 WERS Certified Products Directory - AFRC

NOTES

1. These results are not for public reference can only be used by financial WERS members only.
2. The use of these results requires manufacture validation through the AWA Accreditation Scheme.
3. U_w is the whole window U-value
4. SHGC_w is the whole window solar heat gain coefficient
5. T_{vw} is the whole window visible (light) transmittance
6. Percentage improvement figures are compared with using base-case Generic Window 1 (3mm clear in standard aluminium frame)
7. A negative percentage improvement figure indicates performance worse than the base-case window
8. A positive percentage improvement figure indicates performance better than the base-case window
9. Maximum air infiltration is 5.0L/s.m² at a positive pressure difference of 75 Pa as measured according to AS 2047
10. Static performance (U_w SHGC_w T_{vw} T_{dw}) calculated using Window 7.4 and Therm 7.4 software (LBNL), 1999-2016
11. Annual energy performance (stars and % improvements) calculated using Nationwide House Energy Rating Software (AccuRate) according to procedures of WERS 2008.
12. Results disclosed at Australian Fenestration Rating Council (AFRC) regulations.
13. Products performance is based on products excluding reveals unless "with In-Line Reveal" is included in the product description.
14. Results marked as "with In-Line Reveal" can only be (claimed/used/certified/used for marketing and compliance) when designed, tested, sold, installed and warranted with the reveal in situ. Products that do not include the reveal must revert to the performance excluding the in-line reveal. Please contact the window manufacturer or WERS for further details.



CAP-520 - Thermaglide VS in Futureline 419TB 100mm frame

Aneeta Thermaglide Disclaimer

Source: WERS Certified Product List - Residential - Capral Limited, <https://awawers.net/res/reslist/CAPRALLTD>, accessed 11/09/2020.

Results are shown for a series of combined Aneeta / Capral combined systems. Simulation was organised by Capral, in cooperation with Aneeta, so these results are shown only on the Capral section of the WERS site, using Capral's Window ID's and Frame Descriptions. Aneeta has collated these results in this PDF to share with customers, but the official source is the Capral section of the WERS site.

These results can only be used for the exact window combinations as tested. These results must not be applied to Aneeta inserts in any different frame, nor any other insert in the Capral frames.

Capral Limited

Window ID	Frame	Glazing	Cooling Stars	Heating Stars	Cool%	Heat%	U_w	SHGC _w	T_{vw}	Air Inf
CAP-520-01	Futureline Vertical Sashless Window in 419TB 100mm - Double Glazed	6.38CPGy/12/4Clr	★★★★☆	★★★★☆	64%	44%	2.6	0.32	0.26	0.6
CAP-520-02	Futureline Vertical Sashless Window in 419TB 100mm - Double Glazed	6.38CPClr/12/4Clr	★★★★☆	★★★★☆	55%	51%	2.6	0.45	0.54	0.6
CAP-520-03	Futureline Vertical Sashless Window in 419TB 100mm - Double Glazed	AGG Max ClrLam 6/10/6.38	★★★★☆	★★★★☆	73%	40%	2.3	0.21	0.47	0.6
CAP-520-04	Futureline Vertical Sashless Window in 419TB 100mm - Double Glazed	AGG Max WTransLam 6/10/6.38	★★★★☆	★★★★☆	73%	40%	2.3	0.20	0.36	0.6
CAP-520-05	Futureline Vertical Sashless Window in 419TB 100mm - Double Glazed	AGG Plus ClrLam 6.38/12/4	★★★★☆	★★★★☆	58%	53%	2.3	0.42	0.57	0.6
CAP-520-06	Futureline Vertical Sashless Window in 419TB 100mm - Double Glazed	AGG Plus WTransLam 6.38/12/4	★★★★☆	★★★★☆	64%	49%	2.3	0.34	0.44	0.6
CAP-520-07	Futureline Vertical Sashless Window in 419TB 100mm - Double Glazed	AGG Classic ClrLam 6.38/12/4	★★★☆☆	★★★★☆	47%	51%	3.0	0.53	0.58	0.6
CAP-520-08	Futureline Vertical Sashless Window in 419TB 100mm - Double Glazed	AGG Classic WTransLam 6.38/12/4	★★★★☆	★★★★☆	54%	46%	3.0	0.44	0.44	0.6
CAP-520-09	Futureline Vertical Sashless Window in 419TB 100mm - Double Glazed	AGG Prime ClrLam 4/12/6.38	★★★★☆	★★★★☆	59%	51%	2.5	0.41	0.49	0.6

Search:

Certified Product List - Residential

2020 WERS Certified Products Directory - AFRC

NOTES

1. These results are not for public reference can only be used by financial WERS members only.
2. The use of these results requires manufacture validation through the AWA Accreditation Scheme.
3. U_w is the whole window U-value
4. SHGC_w is the whole window solar heat gain coefficient
5. T_{vw} is the whole window visible (light) transmittance
6. Percentage improvement figures are compared with using base-case Generic Window 1 (3mm clear in standard aluminium frame)
7. A negative percentage improvement figure indicates performance worse than the base-case window
8. A positive percentage improvement figure indicates performance better than the base-case window
9. Maximum air infiltration is 5.0L/s.m² at a positive pressure difference of 75 Pa as measured according to AS 2047
10. Static performance (U_w SHGC_w T_{vw} T_{dw}) calculated using Window 7.4 and Therm 7.4 software (LBNL), 1999-2016
11. Annual energy performance (stars and % improvements) calculated using Nationwide House Energy Rating Software (AccuRate) according to procedures of WERS 2008.
12. Results disclosed at Australian Fenestration Rating Council (AFRC) regulations.
13. Products performance is based on products excluding reveals unless "with In-Line Reveal" is included in the product description.
14. Results marked as "with In-Line Reveal" can only be (claimed/used/certified/used for marketing and compliance) when designed, tested, sold, installed and warranted with the reveal in situ. Products that do not include the reveal must revert to the performance excluding the in-line reveal. Please contact the window manufacturer or WERS for further details.



CAP-521 - Thermaglide VS in Futureline 419TB 150mm frame

Aneeta Thermaglide Disclaimer

Source: WERS Certified Product List - Residential - Capral Limited, <https://awawers.net/res/reslist/CAPRALLTD>, accessed 11/09/2020.

Results are shown for a series of combined Aneeta / Capral combined systems. Simulation was organised by Capral, in cooperation with Aneeta, so these results are shown only on the Capral section of the WERS site, using Capral's Window ID's and Frame Descriptions. Aneeta has collated these results in this PDF to share with customers, but the official source is the Capral section of the WERS site.

These results can only be used for the exact window combinations as tested. These results must not be applied to Aneeta inserts in any different frame, nor any other insert in the Capral frames.

Capral Limited

Window ID	Frame	Glazing	Cooling Stars	Heating Stars	Cool%	Heat%	U_w	SHGC _w	T_{vw}	Air Inf
CAP-521-01	Futureline Vertical Sashless Window in 419TB 150mm - Double Glazed	6.38CPGy/12/4Clr	★★★★☆	★★★★☆	64%	43%	2.7	0.32	0.26	0.6
CAP-521-02	Futureline Vertical Sashless Window in 419TB 150mm - Double Glazed	6.38CPClr/12/4Clr	★★★★☆	★★★★★	54%	50%	2.7	0.45	0.54	0.6
CAP-521-03	Futureline Vertical Sashless Window in 419TB 150mm - Double Glazed	AGG Max ClrLam 6/10/6.38	★★★★★☆☆	★★★★☆	72%	40%	2.4	0.21	0.47	0.6
CAP-521-04	Futureline Vertical Sashless Window in 419TB 150mm - Double Glazed	AGG Max WTransLam 6/10/6.38	★★★★★☆☆	★★★★☆	73%	39%	2.4	0.20	0.36	0.6
CAP-521-05	Futureline Vertical Sashless Window in 419TB 150mm - Double Glazed	AGG Plus ClrLam 6.38/12/4	★★★★☆	★★★★★☆☆	58%	52%	2.4	0.42	0.57	0.6
CAP-521-06	Futureline Vertical Sashless Window in 419TB 150mm - Double Glazed	AGG Plus WTransLam 6.38/12/4	★★★★☆	★★★★☆	64%	48%	2.4	0.34	0.44	0.6
CAP-521-07	Futureline Vertical Sashless Window in 419TB 150mm - Double Glazed	AGG Classic ClrLam 6.38/12/4	★★★☆☆	★★★★★	46%	50%	3.1	0.53	0.58	0.6
CAP-521-08	Futureline Vertical Sashless Window in 419TB 150mm - Double Glazed	AGG Classic WTransLam 6.38/12/4	★★★★☆	★★★★☆	53%	45%	3.1	0.44	0.44	0.6
CAP-521-09	Futureline Vertical Sashless Window in 419TB 150mm - Double Glazed	AGG Prime ClrLam 4/12/6.38	★★★★☆	★★★★★	58%	50%	2.5	0.41	0.49	0.6

Search:

Certified Product List - Residential

2020 WERS Certified Products Directory - AFRC

NOTES

1. These results are not for public reference can only be used by financial WERS members only.
2. The use of these results requires manufacture validation through the AWA Accreditation Scheme.
3. U_w is the whole window U-value
4. SHGC_w is the whole window solar heat gain coefficient
5. T_{vw} is the whole window visible (light) transmittance
6. Percentage improvement figures are compared with using base-case Generic Window 1 (3mm clear in standard aluminium frame)
7. A negative percentage improvement figure indicates performance worse than the base-case window
8. A positive percentage improvement figure indicates performance better than the base-case window
9. Maximum air infiltration is 5.0L/s.m² at a positive pressure difference of 75 Pa as measured according to AS 2047
10. Static performance (U_w SHGC_w T_{vw} T_{dw}) calculated using Window 7.4 and Therm 7.4 software (LBNL), 1999-2016
11. Annual energy performance (stars and % improvements) calculated using Nationwide House Energy Rating Software (AccuRate) according to procedures of WERS 2008.
12. Results disclosed at Australian Fenestration Rating Council (AFRC) regulations.
13. Products performance is based on products excluding reveals unless "with In-Line Reveal" is included in the product description.
14. Results marked as "with In-Line Reveal" can only be (claimed/used/certified/used for marketing and compliance) when designed, tested, sold, installed and warranted with the reveal in situ. Products that do not include the reveal must revert to the performance excluding the in-line reveal. Please contact the window manufacturer or WERS for further details.



CAP-522 - Thermaglide VS in Futureline 440TB frame

Aneeta Thermaglide Disclaimer

Source: WERS Certified Product List - Residential - Capral Limited, <https://awawers.net/res/reslist/CAPALLTD>, accessed 11/09/2020.

Results are shown for a series of combined Aneeta / Capral combined systems. Simulation was organised by Capral, in cooperation with Aneeta, so these results are shown only on the Capral section of the WERS site, using Capral's Window ID's and Frame Descriptions. Aneeta has collated these results in this PDF to share with customers, but the official source is the Capral section of the WERS site.

These results can only be used for the exact window combinations as tested. These results must not be applied to Aneeta inserts in any different frame, nor any other insert in the Capral frames.

Capral Limited

Window ID	Frame	Glazing	Cooling Stars	Heating Stars	Cool%	Heat%	U_w	SHGC _w	T_{vw}	Air Inf
CAP-522-01	Futureline Vertical Sashless Window in 440TB - Double Glazed	6.38CPGy/12/4Clr	★★★★☆	★★★★☆	64%	47%	2.4	0.34	0.28	0.6
CAP-522-02	Futureline Vertical Sashless Window in 440TB - Double Glazed	6.38CPClr/12/4Clr	★★★★☆	★★★★☆	54%	55%	2.4	0.48	0.58	0.6
CAP-522-03	Futureline Vertical Sashless Window in 440TB - Double Glazed	AGG Max ClrLam 6/10/6.38	★★★★☆	★★★★☆	73%	43%	2.1	0.22	0.51	0.6
CAP-522-04	Futureline Vertical Sashless Window in 440TB - Double Glazed	AGG Max WTransLam 6/10/6.38	★★★★☆	★★★★☆	74%	43%	2.1	0.21	0.39	0.6
CAP-522-05	Futureline Vertical Sashless Window in 440TB - Double Glazed	AGG Plus ClrLam 6.38/12/4	★★★★	★★★★☆	57%	57%	2.1	0.45	0.62	0.6
CAP-522-06	Futureline Vertical Sashless Window in 440TB - Double Glazed	AGG Plus WTransLam 6.38/12/4	★★★★☆	★★★★☆	64%	52%	2.1	0.36	0.47	0.6
CAP-522-07	Futureline Vertical Sashless Window in 440TB - Double Glazed	AGG Classic ClrLam 6.38/12/4	★★★☆☆	★★★★☆	44%	54%	2.9	0.57	0.63	0.6
CAP-522-08	Futureline Vertical Sashless Window in 440TB - Double Glazed	AGG Classic WTransLam 6.38/12/4	★★★★☆	★★★★☆	52%	49%	2.9	0.47	0.48	0.6
CAP-522-09	Futureline Vertical Sashless Window in 440TB - Double Glazed	AGG Prime ClrLam 4/12/6.38	★★★★	★★★★☆	58%	54%	2.3	0.44	0.53	0.6

Search:

Certified Product List - Residential

2020 WERS Certified Products Directory - AFRC

NOTES

1. These results are not for public reference can only be used by financial WERS members only.
2. The use of these results requires manufacture validation through the AWA Accreditation Scheme.
3. U_w is the whole window U-value
4. SHGC_w is the whole window solar heat gain coefficient
5. T_{vw} is the whole window visible (light) transmittance
6. Percentage improvement figures are compared with using base-case Generic Window 1 (3mm clear in standard aluminium frame)
7. A negative percentage improvement figure indicates performance worse than the base-case window
8. A positive percentage improvement figure indicates performance better than the base-case window
9. Maximum air infiltration is 5.0L/s.m² at a positive pressure difference of 75 Pa as measured according to AS 2047
10. Static performance (U_w SHGC_w T_{vw} T_{dw}) calculated using Window 7.4 and Therm 7.4 software (LBNL), 1999-2016
11. Annual energy performance (stars and % improvements) calculated using Nationwide House Energy Rating Software (AccuRate) according to procedures of WERS 2008.
12. Results disclosed at Australian Fenestration Rating Council (AFRC) regulations.
13. Products performance is based on products excluding reveals unless "with In-Line Reveal" is included in the product description.
14. Results marked as "with In-Line Reveal" can only be (claimed/used/certified/used for marketing and compliance) when designed, tested, sold, installed and warranted with the reveal in situ. Products that do not include the reveal must revert to the performance excluding the in-line reveal. Please contact the window manufacturer or WERS for further details.



CAP-523 - Thermaglide HS in Futureline 419TB 100mm frame

Aneeta Thermaglide Disclaimer

Source: WERS Certified Product List - Residential - Capral Limited, <https://awawers.net/res/reslist/CAPRALLTD>, accessed 11/09/2020.

Results are shown for a series of combined Aneeta / Capral combined systems. Simulation was organised by Capral, in cooperation with Aneeta, so these results are shown only on the Capral section of the WERS site, using Capral's Window ID's and Frame Descriptions. Aneeta has collated these results in this PDF to share with customers, but the official source is the Capral section of the WERS site.

These results can only be used for the exact window combinations as tested. These results must not be applied to Aneeta inserts in any different frame, nor any other insert in the Capral frames.

Capral Limited

Window ID	Frame	Glazing	Cooling Stars	Heating Stars	Cool%	Heat%	U_w	SHGC _w	T_{vw}	Air Inf
CAP-523-01	Futureline Horizontal Sashless Window in 419TB 100mm - Double Glazed	6.38CPGy/12/4Clr	★★★★☆	★★★★☆	63%	45%	2.6	0.33	0.27	0.6
CAP-523-02	Futureline Horizontal Sashless Window in 419TB 100mm - Double Glazed	6.38CPClr/12/4Clr	★★★★☆	★★★★☆	53%	52%	2.6	0.47	0.57	0.6
CAP-523-03	Futureline Horizontal Sashless Window in 419TB 100mm - Double Glazed	AGG Max ClrLam 6/10/6.38	★★★★☆	★★★★☆	72%	41%	2.2	0.22	0.49	0.6
CAP-523-04	Futureline Horizontal Sashless Window in 419TB 100mm - Double Glazed	AGG Max WTransLam 6/10/6.38	★★★★☆	★★★★☆	73%	41%	2.2	0.21	0.37	0.6
CAP-523-05	Futureline Horizontal Sashless Window in 419TB 100mm - Double Glazed	AGG Plus ClrLam 6.38/12/4	★★★★	★★★★☆	57%	55%	2.3	0.44	0.60	0.6
CAP-523-06	Futureline Horizontal Sashless Window in 419TB 100mm - Double Glazed	AGG Plus WTransLam 6.38/12/4	★★★★☆	★★★★☆	63%	50%	2.2	0.36	0.46	0.6
CAP-523-07	Futureline Horizontal Sashless Window in 419TB 100mm - Double Glazed	AGG Classic ClrLam 6.38/12/4	★★★☆☆	★★★★☆	45%	52%	3.1	0.55	0.61	0.6
CAP-523-08	Futureline Horizontal Sashless Window in 419TB 100mm - Double Glazed	AGG Classic WTransLam 6.38/12/4	★★★★☆	★★★★☆	52%	47%	3.1	0.46	0.47	0.6
CAP-523-09	Futureline Horizontal Sashless Window in 419TB 100mm - Double Glazed	AGG Prime ClrLam 4/12/6.38	★★★★	★★★★☆	57%	52%	2.4	0.43	0.52	0.6

Search:

Certified Product List - Residential

2020 WERS Certified Products Directory - AFRC

NOTES

1. These results are not for public reference can only be used by financial WERS members only.
2. The use of these results requires manufacture validation through the AWA Accreditation Scheme.
3. U_w is the whole window U-value
4. SHGC_w is the whole window solar heat gain coefficient
5. T_{vw} is the whole window visible (light) transmittance
6. Percentage improvement figures are compared with using base-case Generic Window 1 (3mm clear in standard aluminium frame)
7. A negative percentage improvement figure indicates performance worse than the base-case window
8. A positive percentage improvement figure indicates performance better than the base-case window
9. Maximum air infiltration is 5.0L/s.m² at a positive pressure difference of 75 Pa as measured according to AS 2047
10. Static performance (U_w SHGC_w T_{vw} T_{dw}) calculated using Window 7.4 and Therm 7.4 software (LBNL), 1999-2016
11. Annual energy performance (stars and % improvements) calculated using Nationwide House Energy Rating Software (AccuRate) according to procedures of WERS 2008.
12. Results disclosed at Australian Fenestration Rating Council (AFRC) regulations.
13. Products performance is based on products excluding reveals unless "with In-Line Reveal" is included in the product description.
14. Results marked as "with In-Line Reveal" can only be (claimed/used/certified/used for marketing and compliance) when designed, tested, sold, installed and warranted with the reveal in situ. Products that do not include the reveal must revert to the performance excluding the in-line reveal. Please contact the window manufacturer or WERS for further details.



CAP-524 - Thermaglide HS in Futureline 419TB 150mm frame

Aneeta Thermaglide Disclaimer

Source: WERS Certified Product List - Residential - Capral Limited, <https://awawers.net/res/reslist/CAPALLTD>, accessed 11/09/2020.

Results are shown for a series of combined Aneeta / Capral combined systems. Simulation was organised by Capral, in cooperation with Aneeta, so these results are shown only on the Capral section of the WERS site, using Capral's Window ID's and Frame Descriptions. Aneeta has collated these results in this PDF to share with customers, but the official source is the Capral section of the WERS site.

These results can only be used for the exact window combinations as tested. These results must not be applied to Aneeta inserts in any different frame, nor any other insert in the Capral frames.

Capral Limited

Window ID	Frame	Glazing	Cooling Stars	Heating Stars	Cool%	Heat%	U_w	SHGC _w	T_{vw}	Air Inf
CAP-524-01	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	6.38CPGy/12/4Clr	★★★★☆	★★★★☆	64%	41%	2.8	0.31	0.25	0.6
CAP-524-02	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	6.38CPClr/12/4Clr	★★★★☆	★★★★☆	55%	49%	2.8	0.44	0.52	0.6
CAP-524-03	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Max ClrLam 6/10/6.38	★★★★☆	★★★★	72%	38%	2.5	0.20	0.45	0.6
CAP-524-04	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Max WTransLam 6/10/6.38	★★★★☆	★★★★	73%	38%	2.5	0.20	0.34	0.6
CAP-524-05	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Plus ClrLam 6.38/12/4	★★★★☆	★★★★☆	58%	51%	2.5	0.41	0.56	0.6
CAP-524-06	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Plus WTransLam 6.38/12/4	★★★★☆	★★★★☆	64%	46%	2.5	0.33	0.42	0.6
CAP-524-07	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Classic ClrLam 6.38/12/4	★★★	★★★★☆	47%	48%	3.2	0.51	0.56	0.6
CAP-524-08	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Classic WTransLam 6.38/12/4	★★★★☆	★★★★☆	54%	43%	3.2	0.43	0.43	0.6
CAP-524-09	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Prime ClrLam 4/12/6.38	★★★★☆	★★★★☆	58%	48%	2.6	0.40	0.48	0.6

Search: CAP-524

Window ID	Frame	Glazing	Cooling Stars	Heating Stars	Cool%	Heat%	U _w	SHGC _w	T _{v,w}	Air Inf
CAP-524-10	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Prime WTransLam 4/12/6.38	★★★★☆	★★★★★	59%	47%	2.6	0.38	0.36	0.6
CAP-524-11	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Plus Clr 5/12/5	★★★★	★★★★★	57%	51%	2.5	0.43	0.55	0.6
CAP-524-12	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Max Gy 6/12/4	★★★★☆	★★★★	73%	38%	2.4	0.20	0.28	0.6
CAP-524-13	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Classic Clr 5/12/5	★★★☆☆	★★★★★	45%	49%	3.2	0.54	0.56	0.6
CAP-524-14	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Prime Clr 5/12/5	★★★★☆	★★★★★	59%	48%	2.7	0.39	0.47	0.6
CAP-524-15	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Plus Clr 6/12/4	★★★★	★★★★★	57%	51%	2.5	0.42	0.55	0.6
CAP-524-16	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Plus Gy 4/14/4	★★★★☆	★★★★★	65%	45%	2.5	0.31	0.35	0.6
CAP-524-17	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Plus Gy 6/12/4	★★★★☆	★★★★★	68%	42%	2.5	0.26	0.28	0.6
CAP-524-18	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Max Clr 6/12/4	★★★★☆	★★★★★	72%	38%	2.4	0.20	0.45	0.6
CAP-524-19	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Classic Clr 6/12/4	★★★☆☆	★★★★★	45%	49%	3.2	0.54	0.56	0.6
CAP-524-20	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Classic Gy 6/12/4	★★★★☆	★★★★★	58%	39%	3.2	0.36	0.28	0.6
CAP-524-21	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Classic Gy 4/14/4	★★★☆☆	★★★★★	54%	43%	3.2	0.42	0.35	0.6
CAP-524-22	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Prime Gy 6/12/4	★★★★☆	★★★★★	65%	42%	2.6	0.29	0.24	0.6
CAP-524-23	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Prime Clr 4/12/6	★★★★☆	★★★★★	58%	48%	2.6	0.40	0.47	0.6
CAP-524-24	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Prime Gy 4/14/4	★★★★☆	★★★★★	62%	45%	2.7	0.35	0.30	0.6
CAP-524-25	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Plus Clr 4/14/4	★★★☆☆	★★★★★	57%	52%	2.5	0.43	0.56	0.6
CAP-524-26	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Classic Clr 4/14/4	★★★☆☆	★★★★★	44%	50%	3.2	0.55	0.57	0.6
CAP-524-27	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	AGG Prime Clr 4/14/4	★★★★☆	★★★★★	58%	48%	2.7	0.40	0.48	0.6
CAP-524-28	Futureline Horizontal Sashless Window in 419TB 150mm - Double Glazed	4Clr/12Ar/4ET	★★★☆☆	★★★★★	50%	55%	2.6	0.52	0.53	0.6

Showing 1 to 28 of 28 entries (filtered from 2,846 total entries)

Certified Product List - Residential

2020 WERS Certified Products Directory - AFRC

NOTES

1. These results are not for public reference can only be used by financial WERS members only.
2. The use of these results requires manufacture validation through the AWA Accreditation Scheme.
3. U_w is the whole window U-value
4. SHGC_w is the whole window solar heat gain coefficient
5. T_{vw} is the whole window visible (light) transmittance
6. Percentage improvement figures are compared with using base-case Generic Window 1 (3mm clear in standard aluminium frame)
7. A negative percentage improvement figure indicates performance worse than the base-case window
8. A positive percentage improvement figure indicates performance better than the base-case window
9. Maximum air infiltration is 5.0L/s.m² at a positive pressure difference of 75 Pa as measured according to AS 2047
10. Static performance (U_w SHGC_w T_{vw} T_{dw}) calculated using Window 7.4 and Therm 7.4 software (LBNL), 1999-2016
11. Annual energy performance (stars and % improvements) calculated using Nationwide House Energy Rating Software (AccuRate) according to procedures of WERS 2008.
12. Results disclosed at Australian Fenestration Rating Council (AFRC) regulations.
13. Products performance is based on products excluding reveals unless "with In-Line Reveal" is included in the product description.
14. Results marked as "with In-Line Reveal" can only be (claimed/used/certified/used for marketing and compliance) when designed, tested, sold, installed and warranted with the reveal in situ. Products that do not include the reveal must revert to the performance excluding the in-line reveal. Please contact the window manufacturer or WERS for further details.



CAP-525 - Thermaglide HS in Futureline 440TB frame

Aneeta Thermaglide Disclaimer

Source: WERS Certified Product List - Residential - Capral Limited, <https://awawers.net/res/reslist/CAPALLTD>, accessed 11/09/2020.

Results are shown for a series of combined Aneeta / Capral combined systems. Simulation was organised by Capral, in cooperation with Aneeta, so these results are shown only on the Capral section of the WERS site, using Capral's Window ID's and Frame Descriptions. Aneeta has collated these results in this PDF to share with customers, but the official source is the Capral section of the WERS site.

These results can only be used for the exact window combinations as tested. These results must not be applied to Aneeta inserts in any different frame, nor any other insert in the Capral frames.

Capral Limited

Window ID	Frame	Glazing	Cooling Stars	Heating Stars	Cool%	Heat%	U_w	SHGC _w	T_{vw}	Air Inf
CAP-525-01	Futureline Horizontal Sashless Window in 440TB - Double Glazed	6.38CPGy/12/4Clr	★★★★☆	★★★★☆	63%	40%	2.9	0.31	0.25	0.6
CAP-525-02	Futureline Horizontal Sashless Window in 440TB - Double Glazed	6.38CPClr/12/4Clr	★★★★☆	★★★★☆	54%	47%	2.9	0.44	0.52	0.6
CAP-525-03	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Max ClrLam 6.10/6.38	★★★★★	★★★★☆	71%	37%	2.6	0.21	0.45	0.6
CAP-525-04	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Max WTransLam 6.10/6.38	★★★★★	★★★★☆	72%	36%	2.6	0.20	0.34	0.6
CAP-525-05	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Plus ClrLam 6.38/12/4	★★★★★	★★★★☆	57%	49%	2.6	0.41	0.56	0.6
CAP-525-06	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Plus WTransLam 6.38/12/4	★★★★★	★★★★☆	63%	45%	2.6	0.33	0.42	0.6
CAP-525-07	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Classic ClrLam 6.38/12/4	★★★	★★★★☆	46%	46%	3.4	0.52	0.56	0.6
CAP-525-08	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Classic WTransLam 6.38/12/4	★★★★☆	★★★★☆	53%	42%	3.4	0.43	0.43	0.6
CAP-525-09	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Prime ClrLam 4/12/6.38	★★★★★	★★★★☆	58%	47%	2.8	0.40	0.48	0.6

Search:

Window ID	Frame	Glazing	Cooling Stars	Heating Stars	Cool%	Heat%	U _w	SHGC _w	T _{vw}	Air Inf
CAP-525-10	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Prime WTransLam 4/12/6.38	★★★★☆	★★★★☆	59%	46%	2.8	0.38	0.36	0.6
CAP-525-11	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Plus Clr 5/12/5	★★★★☆	★★★★★	56%	50%	2.6	0.43	0.55	0.6
CAP-525-12	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Max Gy 6/12/4	★★★★★	★★★★☆	72%	36%	2.6	0.20	0.28	0.6
CAP-525-13	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Classic Clr 5/12/5	★★★☆☆	★★★★☆	44%	48%	3.4	0.54	0.56	0.6
CAP-525-14	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Prime Clr 5/12/5	★★★★★	★★★★☆	58%	46%	2.8	0.40	0.47	0.6
CAP-525-15	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Plus Clr 6/12/4	★★★★☆	★★★★★	57%	50%	2.6	0.42	0.55	0.6
CAP-525-16	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Plus Gy 4/14/4	★★★★★	★★★★☆	64%	43%	2.6	0.31	0.35	0.6
CAP-525-17	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Plus Gy 6/12/4	★★★★★	★★★★☆	67%	40%	2.6	0.26	0.28	0.6
CAP-525-18	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Max Clr 6/12/4	★★★★★	★★★★☆	72%	37%	2.6	0.20	0.46	0.6
CAP-525-19	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Classic Clr 6/12/4	★★★☆☆	★★★★☆	45%	47%	3.4	0.54	0.56	0.6
CAP-525-20	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Classic Gy 6/12/4	★★★★★	★★★★★	57%	38%	3.4	0.36	0.28	0.6
CAP-525-21	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Classic Gy 4/14/4	★★★★☆	★★★★☆	53%	41%	3.4	0.42	0.35	0.6
CAP-525-22	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Prime Gy 6/12/4	★★★★★	★★★★☆	65%	40%	2.8	0.29	0.24	0.6
CAP-525-23	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Prime Clr 4/12/6	★★★★★	★★★★☆	57%	47%	2.8	0.40	0.47	0.6
CAP-525-24	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Prime Gy 4/14/4	★★★★★	★★★★☆	61%	44%	2.8	0.35	0.30	0.6
CAP-525-25	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Plus Clr 4/14/4	★★★★☆	★★★★★	56%	50%	2.6	0.44	0.56	0.6
CAP-525-26	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Classic Clr 4/14/4	★★★☆☆	★★★★☆	43%	48%	3.4	0.55	0.57	0.6
CAP-525-27	Futureline Horizontal Sashless Window in 440TB - Double Glazed	AGG Prime Clr 4/14/4	★★★★★	★★★★☆	57%	47%	2.8	0.40	0.48	0.6
CAP-525-28	Futureline Horizontal Sashless Window in 440TB - Double Glazed	4Clr/12Ar/4ET	★★★★☆	★★★★★	49%	53%	2.8	0.52	0.53	0.6

Showing 1 to 28 of 28 entries (filtered from 2,846 total entries)